

## A.L.I.C.E. | DATA SHEET

PART	SPECIFICATION	ADDITIONAL INFORMATION
Head tube	44mm	Internal diametre, top and bottom
Headset	ZS44/28.6 (top)	HOPE 2 (Integral); not included
Headset	EC44/40 (bottom, with adapter) or ZS44/30	HOPE H (external) or HOPE B (integrated); not included
Seat collar	34.9mm	Not included
Seat post	30.9mm	Dropper post compatible
Rear axle	142mm (supplied with frame)	M12xP1.75
Bottom bracket	68mm, threaded	External cups/bearings
Chainring size	42T (49mm chainline)	Shimano GRX
Fork length	432mm axle to crown, ALC43ST (-10mm/+0mm)	420mm axle to crown, ALC42CB (-0mm/+10mm)
Dropouts	Sliding dropouts, replaceable	Split dropout for Gates belt
Disc mount/rotor size	Post mount (default), 160mm	Flat mount adaptor (supplied) for mounting caliper
Rotor size/adaptor	Adapter required for 180mm rotors	HOPE L (post 160mm to post 180mm); not included
Wheel size	Frame is optimised for 700c/29er wheels	
Tyre size	Optimised for 29 x 2.1"	Maximum rear tyre, 29 x 2.4" or 27.5 x 2.2"; fork will fit 29 x 2.8"
ED surface treatment	Electrophoretic Deposition (black)	Protects the frame from corrosion (internal/external)
Colours	British Racing Green, Desert, Wonderland Blue	Semi-matte; Gloss (Desert only)